



Safety Data Sheet

Issuing Date: 27 November 2014

Revision Date: 18 November 2022

Revision Number: 4

1. Identification of the Substance/Preparation and the Company Undertaking

GHS Product Identifier

Product Name Super Met-AI Rolling Bull Stainless Steel Tip Paint Marker

Other Means of Identification

Part Number

Bulk: 78100 White, 78101 Yellow, 78102 Black, 78103 Red, 78104 Blue, 78105 Green, 78106 Orange

Carded: 78150 White, 78151 Yellow, 78152 Black, 78153 Red, 78154 Blue, 78155 Green, 78156 Orange

Colors: WHITE, YELLOW, BLACK, RED, BLUE, GREEN, ORANGE

Formula Code SKM

Synonyms none

Recommended use of the chemical and restrictions on use

Recommended Use Marker

Uses Advised Against No information available

Supplier's Details

Supplier Address

SKM Industries Inc.
1012 Underwood Road
Olyphant, Pa 18447
Telephone: 570-383-3062

Emergency Telephone Number

Chemtrec US & Canada 800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communications Standard 2012 (29 CFR 1910.1200)

Flammable Liquid Category 3

GHS Label Elements, including precautionary statements

Emergency Overview

Signal Word – Warning

Hazard Statements –

Skin irritation

Eye irritation

Respiratory irritation

Harmful by inhalation

May be harmful if swallowed

Flammable liquid and vapor

Toxic to aquatic organisms



Appearance – Opaque, varies
Physical state- Thin viscosity liquid
Odor – Aromatic Odor

Precautionary Statements

Prevention

Do not handle until all safety precautions have been read and understood
Obtain special instructions before use
Keep container tightly closed
Use only in a well ventilated area
Do not breathe dust/vapors/fumes
Wash face and hands and any exposed skin thoroughly after handling
Wear protective gloves/clothing/eye protection/face protection
Keep away from heat/sparks/flame hot surfaces – no smoking
Use explosion proof electrical/ventilating/lighting equipment
Ground/bond container and receiving equipment.
Use non sparking tools
Take precautionary measures against static discharge

Response:

If exposed or concerned: get medical attention/advice.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
If swallowed: Immediately call a poison center/doctor. Do not induce vomiting.
In case of fire: Use CO₂, dry chemical, foam or water spray to extinguish.

Storage:

Store in a well-ventilated place.
Keep cool.
Store locked up.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS No.	OSHA PEL	ACGIH-TLV	Other Limits	
				Recommended	%
Aromatic Hydrocarbon	64742-95-6	TWA 100 ppm	TWA 100 ppm	No Data	20-35
Clay, Silica	1332-58-7	15 mg/m ³	TWS 15 mg/m ³	No Data	15-20
1,2,4 Trimethyl Benzene	95-63-6	TWA 100 ppm	TWA 100 ppm	No Data	1-10
Xylene	1330-20-7	TWA 100 ppm	TWA 100 ppm	No Data	1-5
Hydrocarbon Resin	Proprietary	Nonhazardous	No Data	No Data	15-20
May contains one or more of the following...					
Titanium Dioxide	13463-67-7	TWA 10 mg/m ³	TWA 10 mg/m ³	No Data	1-30
PNC Green Pigment	1328-53-6	TWA 10 mg/m ³	TWA 10 mg/m ³	No Data	1-10

Carbon Black	1333-86-4	TWA 3.5 mg/m ³	TWA 3.5 mg/m ³	No Data	1-10
PCN Blue Pigment	147-14-8	TWA 10 mg/m ³	TWA 10 mg/m ³	No Data	1-10
Disazo Orange	15793-73-4	No data	No data	No Data	1-10
Organic Yellow(s)	6358-31-2 6528-34-3	TWA 10 mg/m ³	TWA 10 mg/m ³	No Data	1-10
Pigment Red	2786-76-7	TWA 15 mg/m ³	TWA 15 mg/m ³	No Data	1-5
Pigment Orange	36 12236-62-3	TWA 10mg/m ³	TWA 10mg/m ³	No Data	1-5
Pigment Yellow	154 68134-22-5	TWA 15 mg/m ³	TWA 15 mg/m ³	No Data	1-5

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice	Combustible liquid and vapor. Keep away from heat, sparks, and flames. May cause eye, skin and respiratory tract irritation. If swallowed do not induce vomiting. Get immediate medical attention. In case of doubt, or when symptoms persist, seek medical attention.
Eye Contact	Immediately flush eyes with plenty of water for at least fifteen (15) minutes. Get medical attention immediately.
Skin Contact	Flush skin with plenty of water. Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleanser.
Inhalation:	Remove to fresh air, keep patient warm and at rest. If breathing is irregular seek medical advice. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention immediately.
Ingestion	Seek medical attention immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Protection of First Aiders Use personal protection equipment.

Most important symptoms/effects, acute and delayed

Most important symptoms/effects Prolonged or repeated contact may cause skin sensitization or dermatitis. Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage. Intentional misuse by deliberately concentrating or inhaling this product may be harmful or fatal. IARC (International Agency for Research of Cancer) has classified Carbon Black and Titanium Dioxide as a possible human carcinogen (2B).

Indication of immediate medical attention and special treatment needed, if necessary

Note to physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use water fog, dry chemical, carbon dioxide or foam. Use water spray to cool fire-exposed containers and to protect personnel.

Unsuitable extinguishing media No information available

Specific Hazards arising from the chemical No information available

Flash Point: 108°F

Flammability Limits (% by volume): LEL 1.9 UEL 12.3

Unusual Fire Explosion Hazards: Vapors are heavier than air and may travel along ground, or be moved by ventilation and be ignited by ignition source

Protective Equipment and Precautions for Firefighters

Wear appropriate self-contained breathing apparatus MSHA/NIOSH (approved or equivalent) and full protective gear. Cool closed containers exposed to fire with water spray. Avoid inhalation of material or combustion by-products; stay upwind. Prevent spill from entering drains, sewers, streams or other bodies of water. If run-off occurs, notify proper authorities

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid breathing vapours. Evacuate personnel to safe areas. Ensure adequate ventilation.

Environmental Precautions Avoid release into the environment. Do not allow to enter drains or watercourses.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Evacuate area of unprotected personnel.

Methods for Cleaning Up Contain and absorb the spillage with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth to soak up the product and place in a suitable container for disposal in accordance with the waste regulations. Prevent spill from entering drains, sewers, streams or other bodies of water. If run-off occurs, notify proper authorities. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Dispose of properly in compliance with federal, state, and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Avoid skin and eye contact. Avoid the inhalation of vapor and mist. Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, sparks, flames, static electricity, or other sources of ignition. Many hot organic chemical vapors or mists are susceptible to sudden spontaneous combustion when mixed with air. Ignition may occur at temperatures below those published in the literature as "auto-ignition" or ignition temperatures. Ignition temperatures decrease with increasing vapor volume and vapor volume and vapor/air contact time, and are influenced by pressure changes. Ignition of organic chemical vapors may occur at typical elevated-temperature process conditions, especially in processes operating under vacuum if subjected to sudden ingress of air, or outside process equipment operating under elevated pressure if sudden escape of vapors or mists to the atmosphere occurs. Any proposed use of this product in elevated- temperature processes should

be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Conditions for safe storage, including any incompatibilities

Storage	Keep away from heat, sparks and open flames. Keep out of reach of children. Keep container tightly sealed when not in use. Store in cool, well-ventilated place away from incompatible materials. Information on this Material Safety Data Sheets refers to ink used in pens and markers; however, it applies to these inks in bulk. The inks are contained in capillary or valve reservoirs and will not spill or leak under normal conditions
Incompatible products	Strong oxidizing and reducing agents, strong alkali and strong acids

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Appropriate engineering controls

Engineering Measures	Showers, eyewash stations, ventilation systems Local Exhaust: Not usually needed; Mechanical (General): Yes; Special/Other: None
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/Face protection	None under normal use conditions. Avoid eye contact. Wear chemical splash goggles in compliance with OSHA regulation if splashing is possible.
Skin and body Protection	None under normal use conditions. Avoid repeated or prolonged contact with skin. Wear impervious gloves if needed to prevent possible skin irritation
Respiratory Protection	None under normal use conditions. If irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Use with adequate ventilation. Use NIOSH/MSHA approved respirator if PELs or TLVs are exceeded. No special ventilation is normally required.
Hygiene Measures	Use in a well-ventilated area. When using do not eat, drink, or smoke. Provide regular cleaning of equipment, work areas and clothing. For bulk material, if direct contact is possible, wear apron, boots, face shield, etc. as needed. Follow label instructions. Wash hands after use and before eating, drinking, smoking, using restrooms, etc.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

<u>Property</u>	<u>Value</u>
BOILING POINT	318 to 338 °F
SPECIFIC GRAVITY (H ₂ O= 1)	>1 @ 70°F
VAPOR PRESSURE (mm-Hg @ 70°F)	No Data
MELTING POINT	No Data
VAPOR DENSITY (AIR =1)	Greater than (1)
EVAPORATION RATE (Butyl Acetate=1)	Less than one (1)
SOLUBILITY IN WATER	Slight
pH:	No Data
APPEARANCE	Opaque, thick viscosity liquid
ODOR	Aromatic odor

10. STABILITY AND REACTIVITY

Reactivity	No data available
Chemical Stability	Stable under normal storage and handling conditions
Possibility of Hazardous reactions	None under normal use
Hazardous Polymerization	Will not occur
Conditions to Avoid	Heat, open flame, sparks, and sources of ignition
Incompatible Materials	Strong oxidizing and reducing agents, strong alkalis and strong acids
Hazardous Decomposition -products	Carbon dioxide, carbon monoxide, smoke, soot and various oxidation by-products.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information None available. There is no data available on the product itself. None of the components of this product are listed as a carcinogen or suspected carcinogen or is considered a reproductive hazard

Chemical	LD50 oral	LD50 Dermal	LD50 Inhalation
Xylene	3500 mg/kg rat	4350 mg/kg rabbit	29.08 mg/l rat
Titanium dioxide	1000 mg/kg rat	-	-

12. ECOLOGICAL INFORMATION

Ecotoxicity There is no data available on the product itself

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Discard empty pen in trash and dispose of in accordance with all applicable local, state and federal regulations. The liquid contents of the pen meet the definition of hazardous waste under RCRA, D001 (ignitable).

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

(Not mean to be all inclusive)

DOMESTIC HIGHWAY (Containers < 1 Quart are Consumer Commodity)

PROPER SHIPPING NAME:Paint

HAZARD CLASS/SUBSIDIARY HAZARD: 3

UN/NA NO. UN1263

PACKING GROUP: III

LABEL REQUIRED:Combustible Liquid (2)

DOMESTIC AIR SHIPMENTS (PENS)

PROPER SHIPPING NAME:Consumer Commodity

HAZARD CLASS/SUBSIDIARY HAZARD: 9

UN/NA NO. I.D. 8000

PACKING GROUP: None

LABEL REQUIRED:Class 9

15. REGULATORY INFORMATION

(Not meant to be all inclusive- selected regulations represented)

U.S. FEDERAL REGULATIONS:

CARCINOGENICITY: NTP: No IARC Monographs:2B OSHA Regulations: No

OSHA: Hazardous by definition of Hazard Communications Standard (29 CFR 1910.1200)

SECTION 313 REPORTING REQUIREMENTS: This product contains Xylene (1330-20-7) and 1,2,4 Tri Methyl Benzene (95-63-6) which are listed and may require reporting under SARA Title III Sec. 313 if used over the threshold reporting quantity. This information must be included in all MSDSs that are copied and distributed for this material.

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS: Not WHMIS controlled (pens)

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65: WARNING: This product contains a chemical known to the State of California to cause cancer. Benzene, Ethyl benzene

16. OTHER INFORMATION

Health Hazard 2

Flammability 2

Reactivity 0

Personal Protection B

SKM has been advised by attorney that the OSHA Hazard Communication Standard does not apply to the SKM products listed in this SDS. The explanation for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2002 per the code of Federal Regulations. This information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the Hazard Communication Standard covers the product nor is this SDS meant to comply with all requirements of the Hazard Communication Standard.

End of Safety Data Sheet